

45°F+

CAUTIONS CONTAINS

SHERWIN-WILLIAMS 702465
912-638-0022

05/28/20

Order # 0156261

Application.

Wood Prime
Superior Oil-Base

LIENCE
IN

ARCHITECTURAL
ACRYLIC

COROB MODULA HF

coat of the app
d surfaces requi
5°F, substrates n
ure the air, surfac
F and at least 5°F a
ow is expected in
surface temperatu
On large expanses
terial temperatures

OMP (B011) 670 GULF STREAM

CUSTOM SHER-COLOR MATCH

*COLORANT
-White
-Blue
-3-Deep Gold

	0Z	32	64	128
-White	-	59	1	1
-Blue	-	26	1	-
-3-Deep Gold	-	9	1	1

polyester brush
-3/4" nap synt
essure: 2000

QUART
K43W00053

MV

DEEP
640413571

NOT RECOMMENDED FOR USE ON VINYL

this coating
w on the surfac
ology allows yo
s concern abou

FO:
Do not pr
recycling.

CAUTION: Returnable Tinted Col
always To
the j rde
of th n
mixe int

ventria
eye wa-
zziness,
near re-
SH ap-
1. Avoid
n. Wash
ontainer
Do not
er con-
ST AID:
t, flush
amounts
ention if
allowed,
er, hos-
or physi-
ARNING:
hemicals
California
with de-
ve harm.
RNALLY.
CH OF
24 (1/10)

Ingredients
Water
37-39
Titanium
(1314-52-2)
VOC
25